



WXECPP210

FUNI

Protezione anticaduta



Benefici



Igiene

• Imbracature e tessuti possono essere lavati con sapone neutro.



Facilità d'uso

• Moschettoni automatici per una chiusura sicura e senza sprechi di tempo

Campi di utilizzo

- Lavori pubblici
- Edificio
- Finitura / artigiani
- Petrolio e gas minerario (estrazione)

Certificazioni e norme



IRAM 3622-2

Protegge contro i rischi



Caduta



WXECPP210

FUNI

Protezione anticaduta

Dettagli - Norme

Dettagli tecnici

Composizione del supporto principale	Acciaio, Poliestere
Lunghezza massima (m)	0,95 m
Lunghezza minima (m)	0,70 m
Regolazione	Fibbia di regolazione
Colore	Nero-Rosso
Connettore (lato struttura)	2 connettori a chiusura automatica, acciaio, apertura 55 mm
Durata di vita a partire dalla data di fabbricazione (anni)	10
Situazioni di lavoro	Posizionamento al posto di lavoro, Trattenuta



Fall protection

WXECP210

LANYARDS

Double fastening and positioning tether. Adjustable length from 0.70 m to 0.95 m. With 55 mm carabiners for maximum versatility. This PPE is not designed to arrest falls.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXECP210	Black-Red	1 m	WXECP210	7798408755617	0	10	1	11.3 kg	38.0 cm	25.0 cm	17.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height