



Fall protection

WXECPP210

LANYARDS

Double fastening and positioning tether. Adjustable length from 0.70 m to 0.95 m. With 55 mm carabiners for maximum versatility. This PPE is not designed to arrest falls.



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Ease of Use

- Automatic carabiners for secure locking and time saving

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Oil & Gas (Extraction)

Certifications and norms



IRAM 3622-2

Risk Protection



Fall



Fall protection

WXECPP210

LANYARDS

Double fastening and positioning tether. Adjustable length from 0.70 m to 0.95 m. With 55 mm carabiners for maximum versatility. This PPE is not designed to arrest falls.

Standards - Details

Technical details

Composition of the main support	Steel, Polyester
Max. length (m)	0,95 m
Min. length (m)	0,70 m
Adjustment	Adjustment loop
Color	Black-Red
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Fall arrest work situations	Work positioning, Restraint



Fall protection

WXECP210

LANYARDS

Double fastening and positioning tether. Adjustable length from 0.70 m to 0.95 m. With 55 mm carabiners for maximum versatility. This PPE is not designed to arrest falls.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WXECP210	Black-Red	1 m	WXECP210	7798408755617	0	10	1	11.3 kg	38.0 cm	25.0 cm	17.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height