



ANSI506

FALL ARRESTER HARNESES

Fall protection



Specific benefits



Comfort

- "H" configuration for greater comfort in women and men
- Thermoformed belt provides lumbar support and optimal comfort



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 140kg



Ease of Use

- Ergonomic design facilitates user movement
- NFC system guarantees traceability

Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage

Certifications and norms

ANSI Z359.11-2014

ANSI Z359.11-2021

Risk Protection



Fall



Electrical



ANSI506

FALL ARRESTER HARNESES

Fall protection

Standards - Details

Technical details

Type of equipment	Fall arrester harness - dielectric
Composition of the main support	ABS, Steel, Polyester
Strap width (mm)	45 mm
Fastening	Buckles
Number of attachment points	2
Number of total holding attachment points	2
Buckles	Manual loop
Anti-fall point	Dorsal, Sternal
Holding point	Lateral
Size	M/L
Lifespan from manufacturing (years)	10
Type of conditioning	Box of 5
Number of fall arrest anchorage points	2
Sternal	1
Dorsal	1
Fall arrest work situations	Vertical movement on a permanent structure, Work positioning, Movement on lifeline, Restraint, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



ANSI506

FALL ARRESTER HARNESES

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI506	Black-Yellow	M/L	ANSI506	7798408752838	0	5	5	12.1 kg	40.0 cm	35.0 cm	28.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height