



ANSI553

UPRTAČI

Oprema protiv pada



Prednosti



Udobnost

- Termoformirani pojas pruža lumbalnu potporu i optimalnu udobnost



Higijena

- Mogućnost pranja pojaseva i tkanine neutralnim sapunom



performanse

- Certificirano za maksimalno nazivno opterećenje veće od 100 kg: proizvod certificiran za 140 kg



Jednostavnost korištenja

- Ergonomski dizajn koji olakšava kretanje korisnika
- NFC sustav koji jamči sljedivost
- #MUSPEC

Certifikati i standardi

ANSI Z359.11-2021

Područje upotrebe

- Zgrada
- Održavanje
- Kemijska industrija
- Petrokemija
- Skladištenje

Štiti od



Pad



Električni



ANSI553

UPRTAČI

Oprema protiv pada

Pojedinosti - Standardi

Tehnički detalji

Vrsta opreme	Dielektrični uprtač
Ukupan broj točaka za pričvršćivanje	2
Broj točaka pričvršćivanja za pozicioniranje	2
Točka pričvršćivanja za zaustavljanje pada	Leđni, Prsni
Točke pričvršćivanja za pozicioniranje	bočni
Vijek upotrebe nakon datuma proizvodnje (godine)	10
Broj sidrišnih točaka za zaustavljanje pada	2
Radne situacije za zaštitu od pada	Vertikalno kretanje na fiksnoj strukturi, Pozicioniranje na mjestu rada, Kretanje na horizontalnom sustavu učvršćenja (lifeline), Zadržavanje, Dugotrajno vertikalno kretanje ili kretanje na kosoj podlozi, Dugotrajno vertikalno kretanje ili kretanje na kosoj podlozi za radove na užetu, Kratkotrajno vertikalno kretanje ili kretanje na kosoj podlozi (- 3m), Dugotrajno horizontalno kretanje na horizontalnoj podlozi, Dugotrajno horizontalno kretanje na vertikalnoj podlozi, Kratkotrajno horizontalno kretanje (- 3m), Dugotrajno kretanje s mogućnošću pomjeranja točke pričvršćivanja



ANSI553

FALL ARRESTER HARNESSES

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI553	Black-Yellow	M/L	ANSI553	7798408753484	0	5	5	11.6 kg	40.0 cm	30.0 cm	30.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height