



ANSI527

ENERGY ABSORBING LANYARDS

Fall protection



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg



Easy to use

- Automatic carabiners for secure and time-saving locking
- NFC system guarantees traceability

Certifications and norms

ANSI Z359.13-2013 (R2022)

Applications

- Building
- Maintenance
- Chemical industry
- Petrochemical
- Storage

Protects against risks



Fall



ANSI527

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Steel, Polyester
Strap width (mm)	30
Length (m)	1,8
Color	Black-Yellow
Connector (user side)	Automatic lock hook, steel, opening 22mm
Connector (structure side)	Self-locking hook, steel, opening 60 mm
Lifespan from manufacturing (years)	10
Type of packaging	Box of 10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	5.9055



ANSI527

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI527	Black-Yellow	1,8 m	ANSI527	0	0	10	1	16.52 kg	38.0 cm	25.0 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height