



ANSI533

ENERGY ABSORBING LANYARDS

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg; product certified at 140kg



Ease of Use

- Automatic carabiners for secure locking and time saving
- NFC system guarantees traceability

Certifications and norms

ANSI Z359.13-2013 (R2022)

Applications

- Building
- Maintenance
- Chemical Industry
- Petrochemical
- Storage

Risk Protection



Fall



ANSI533

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Max. length (m)	1,8 m
Strap width (mm)	30 mm
Length (m)	1,8
Color	Black-Yellow
Connector 1	Automatic lock hook, steel, opening 22mm
Connectors (structure side)	2 automatic lock hooks, steel, opening 60mm
Lifespan from manufacturing (years)	10
Type of conditioning	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	5.9055



ANSI533

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
ANSI533	Black-Yellow	1,8 m	ANSI533	0	0	5	1	13.02 kg	38.0 cm	25.0 cm	17.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height