



ANSILV5160

FALL ARRESTERS ON ROPE

Fall protection



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg; product certified at 140kg

Applications

- Building
- Oil & Gas (Extraction)
- Power Energy
- Storage

Certifications and norms

Risk Protection



Fall



ANSILV5160

FALL ARRESTERS ON ROPE

Fall protection

Standards - Details

Technical details

Anchoring device	Lifeline
Composition of the main support	Polyamide
Max. length (m)	100 m
Min. length (m)	10 m
Rope diameter (mm)	16
Color	White
Lifespan from manufacturing (years)	10
Diameter (mm)	16



ANSILV5160

FALL ARRESTERS ON ROPE

Fall protection

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
ANSILV5160100	White	10 m	ANSILV516O	0	0	1	1	1.68 kg	38.0 cm	25.0 cm	11.0 cm
ANSILV5160200	White	20 m	ANSILV516O	0	0	1	1	3.12 kg	38.0 cm	25.0 cm	17.0 cm
ANSILV5160300	White	30 m	ANSILV516O	0	0	1	1	4.38 kg	38.0 cm	25.0 cm	17.0 cm
ANSILV5160400	White	40 m	ANSILV516O	0	0	1	1	5.8 kg	38.0 cm	25.0 cm	25.0 cm
ANSILV5160500	White	50 m	ANSILV516O	0	0	1	1	6.92 kg	40.0 cm	30.0 cm	30.0 cm
ANSILV5160800	White	80 m	ANSILV516O	0	0	1	1	11.0 kg	40.0 cm	35.0 cm	28.0 cm
ANSILV5161000	White	100 m	ANSILV516O	0	0	1	1	0.0 kg	0.0 cm	0.0 cm	0.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height